



VIMLOC



Electronic Hotel Locks

Electronic Locks



VL80-V02MF

*Electronic interior lock, made of stainless steel 304.
It is powered by four AA type alkaline batteries.
European type mechanism and Anti-Panic function.
It has a mechanical key in case of emergency.
CE certified.
Available in silver and gold.
Compatible with Mifare technology cards.
It is possible to issue building, floor
and visitor Master cards. Features a low battery alert.
Battery life: about one year.*

Battery life	10000 openings
Motor duration	100000 openings
SC	<25 μ A
DC	<200 mA
Humidity	15 - 90 % RH
Panel size	W76.5 x H242 x D66 mm

*Electronic interior and exterior lock,
made of stainless steel 304.
It is powered by four AA type alkaline batteries.
European type mechanism and Anti-Panic function.
It has a mechanical key in case of emergency.
CE certified.
Available in silver and gold.
Compatible with Mifare technology cards.
It is possible to issue building, floor
and visitor Master cards. Features a low battery alert.
Battery life: about one year.*

VL81-V05MF



Battery life	10000 openings
Motor duration	100000 openings
SC	<25 μ A
DC	<200 mA
Humidity	15 - 90 % RH
Panel size	W76,6 x H305 x D72 mm

Electronic Locks



OA-SMART-MF

*Electronic interior and exterior lock,
made of stainless steel 304.*

Ideal for aluminum doors.

It is powered by four AAA alkaline batteries.

European type mechanism.

It has a mechanical key in case of emergency.

CE certified. Available in silver.

Compatible with Mifare technology cards.

*It is possible to issue building, floor
and visitor Master cards. Features a low battery alert.*

Battery life	12 to 18 months
Suitable door thickness	32 to 70 mm
SC	<10 μ A
DC	<100-150 mA
Humidity	20 - 90 % RH
Panel size	W40 x H280 x D13 mm

*Electronic interior and exterior lock,
made of stainless steel 304.*

Ideal for aluminum doors.

It has led with green / red color for indication of current status.

It is powered by four AAA type alkaline batteries.

European type mechanism and Anti-Panic function.

It has a mechanical key in case of emergency.

CE certified.

Available in silver and gold.

Compatible with Mifare technology cards.

*It is possible to issue building, floor
and visitor Master cards. Features a low battery alert.*

YK99-V39MF



Battery life	15000 openings
Memory	1000 events
SC	<20 μ A
DC	<150 mA
Humidity	15 - 90 % RH
Panel size	W45 x H300 x D20 mm

Electronic Locks



YK99-V36MF

*Electronic interior lock, made of stainless steel 304.
It is powered by four AA type alkaline batteries.
European type mechanism and Anti-Panic function.
It has a mechanical key in case of emergency.
CE certified. Available in silver, gold and black.
Compatible with Mifare technology cards.
It is possible to issue building, floor
and visitor Master cards. Features a low battery alert.*

Battery life	15000 openings
Memory	1000 events
SC	<20 μ A
DC	<150 mA
Humidity	15- 90 % RH
Panel size	W75 x H290 x D25 mm

*Electronic indoor bluetooth lock,
with high aesthetics and durable illuminated
touch keyboard with password entry function.
LED screen for usability.
With free addition and deletion of codes.
It is powered by four AA type alkaline batteries.
It has a mechanical key for an emergency.
CE certified. Features a low battery alert.*

TY-90-V06BT





Encoder

RF smart card encoder and reader (encoder).

Battery life	12 to 18 months
Suitable door thickness	32 to 70 mm
SC	<10 μ A
DC	<100-150 mA
Humidity	20 - 90 % RH
Panel size	W40 x H280 x D13 mm

Ηλεκτρονική κλειδαριά εσωτερικού και εξωτερικού χώρου, από ανοξείδωτο ατσάλι 304. Ιδανική για πόρτες αλουμινίου. Διαθέτει led με πράσινο/κόκκινο χρώμα για ένδειξη κατάστασης

Τροφοδοτείται με τέσσερις αλκαλικές μπαταρίες τύπου AAA. Μηχανισμός ευρωπαϊκού τύπου και Anti-Panic λειτουργία. Διαθέτει μηχανικό κλειδί για περίπτωση έκτακτης ανάγκης.

Πιστοποιημένη με CE.

Διαθέσιμη σε ασημί και χρυσό. Συμβατή με κάρτες τεχνολογίας Mifare.

Υπάρχει η δυνατότητα έκδοσης καρτών Master, κτιρίου, ορόφου, επισκέπτη.

Διαθέτει ειδοποίηση χαμηλής μπαταρίας.

YK99-V39MF



Battery life	15000 openings
Memory	1000 events
SC	<20 μ A
DC	<150 mA
Humidity	15 - 90 % RH
Panel size	W45 x H300 x D20 mm