



TX-V20GR-V42B

External Dimensions H x W x D mm	200 x 418 x 370
Weight kg	9,3
Capacity liters	25
Box sheet metal thickness mm	1,5
Door sheet metal thickness mm	5
Holes for mounting back / base	4/4

With electronic type keyboard and hotel closing / opening function.

It has a light 6-digit LED display , with the ability to place codes 4-6 digits by the visitor with display of digits on the screen.

Ability to open with Master key or Master code or by using the optional CEU device in case of need. It also has an audio and visual indication of low battery voltage and interior lining with carpet on the floor.

Power supply with 4 batteries LR6 / AA1.5V.

Lock with two stainless steel bolts 20mm in diameter. Finishing with electrostatic painting of high-strength polyester epoxy powder.

- * With the possibility of using the optional CEU device
- * With the possibility of internal lighting led when the door opens

It has an electronic keyboard and knob, with the ability to place codes of 4-6 digits by the visitor. No hotel function.

Can be opened with a mechanical Master key in case of emergency. It has audio and visual indication of low battery voltage and internal lining with carpet on the floor. Power supply with 4 batteries LR6 / AA 1.5V (included). Lock with two steel bolts.

YA-VL20GR



External Dimensions H x W x D mm	200 x 310 x 200
Weight kg	7,5
Capacity liters	10
Box sheet metal thickness mm	1,5
Door sheet metal thickness mm	4
Holes for mounting back / base	4/4



YA-VL2044GR

External Dimensions H x W x D mm	200 x 435 x 365
Weight kg	12,6
Capacity liters	26
Box sheet metal thickness mm	2
Door sheet metal thickness mm	5
Holes for mounting back / base	4/4

With electronic keyboard and hotel
closing / opening function.
It has a bright 6-digit LED display,
with the ability to place codes of 4-6 digits
by the visitor and display digits on the screen.
Possibility of opening with Master key or Master code
or by using the optional CEU device
in case of emergency.
It also has audio and visual indication of low
battery voltage and internal carpeting on the floor.
Power supply with 4 batteries LR6 / AA 1.5V (included).
Lock with two stainless steel bolts 20 mm in diameter.
Finishing with electrostatic painting of
high-strength polyester epoxy powder.

- * With the possibility of using the optional CEU device
- * With the possibility of internal lighting led when the door opens

It has an electronic keyboard and knob, with the ability to place codes of 4-6 digits by the visitor. No hotel function.

Can be opened with a mechanical
Master key in case of emergency.
It has audio and visual indication of low battery
voltage and internal lining with carpet on the floor.
Power supply with 4 batteries
LR6 / AA 1.5V (included).
Lock with two steel bolts.

YA-VL25GR



External Dimensions H x W x D mm	250 x 350 x 200
Weight kg	9,5
Capacity liters	14
Box sheet metal thickness mm	1,5
Door sheet metal thickness mm	4
Holes for mounting back / base	4/4



TX-V20GR-V35B

External Dimensions H x W x D mm	200 x 350 x 200
Weight kg	6,4
Capacity liters	9,8
Box sheet metal thickness mm	1,5
Door sheet metal thickness mm	4
Holes for mounting back / base	4/4

and hotel closing / opening function.

It has a light 6-digit LED display , with the ability to place codes 4-6 digits by the visitor with display of digits on the screen.

Ability to open with Master key or Master code or by using the optional CEU device in case of need. It also has an audio and visual indication of low battery voltage and interior lining with carpet on the floor.

Power supply with 4 batteries LR6 / AA1.5V.

Lock with two stainless steel bolts 20mm in diameter. Finishing with electrostatic painting of high-strength polyester epoxy powder.

- * With the possibility of using the optional CEU device
- * With the possibility of internal lighting led when the door opens

Safe - Drawer with electronic keyboard.

Possibility of placing codes of 4-6 digits by the visitor. Possibility of opening with a mechanical Master key in case of emergency.

It has audio and visual indication of low voltage battery. Power supply with 4 batteries LR6 / AA 1.5V (included). It has an interior lining with carpet on the floor. Lock with two steel bolts.

- * With the possibility of using the optional CEU device
- * With the possibility of internal lighting led when the door opens



External Dimensions H x W x D mm	200 x 508 x 381
Weight kg	17
Capacity liters	18,9
Box sheet metal thickness mm	2
Door sheet metal thickness mm	5
Holes for mounting back / base	4/4



External Dimensions H x W x D mm	200 x 508 x 381
Weight kg	10
Capacity liters	10,7
Box sheet metal thickness mm	1,5
Door sheet metal thickness mm	5
Holes for mounting back / base	-/4

With electronic type keyboard and hotel closing / opening function. It has a light 6-digit LED display, with the ability to place codes 3-8 digits by the visitor with display of digits on the screen. Automatic lock after three consecutive incorrect opening attempts. Ability to open with Master key or Master code in case of need.

Power supply with 4 batteries LR6 / AA1.5V. It also has an audio and visual indication of low battery voltage and interior lining with carpet on the floor. Lock with two stainless steel bolts.

Finishing with electrostatic painting of high-strength polyester epoxy powder.

- * With the possibility of using the optional CEU device
- * With the possibility of internal lighting led when the door opens

It has an electronic keyboard and knob, with the ability to place codes of 4-6 digits by the visitor. No hotel function.

Can be opened with a mechanical Master key in case of emergency. It has audio and visual indication of low battery voltage and internal lining with carpet on the floor. Power supply with 4 batteries LR6 / AA 1.5V.

Lock with two steel bolts.





External Dimensions H x W x D mm	200 x 430 x 365
Weight kg	10,5
Capacity liters	25
Box sheet metal thickness mm	2
Door sheet metal thickness mm	4
Holes for mounting back / base	4/4



Optional device that sets the room number, date and time in the safe, unlocks the safe in case of emergency and also reads and stores the number of openings in the safe with data.

It can be used with the following safes:

YA-VL2200G

YA-VL2244GR

TX-VL3520

TX-VL5040

TX-U12_V40